GF-HV Test

Gravity Feed High Voltage



Specifications

Test Station

- Single Test Site
- Ambient Test Condition
- Max Voltage 20KV
- AC or DC Test Interface
- Max No. of Test Components: 6

Sorting

- Ball Screw Drive with 10um Accuracy
- Software Programmable Sorting Position

HMI

- Touch Screen LCD With Start Stop Button
- Multi Level Password For Data Protection
- Input / Output Check Function Included
- Manual Function For Troubleshooting

Handler <-- > Tester Communication

- RS232, TTL, GPIB

Utilities

- Power: 200 to 250Vac 50/60Hz 16A max
- CDA: 5 bar

- UPH Up To 10K (6 components/site)
- Auto Unloading Input: 40pcs Tube Capacity
- Auto Loading Output: 40pcs Tube Capacity
- Reject Tube: Up To 5 Tubes With Sensor Detection
- Event Monitoring Option With Memory Card
- Supports csv, xls, xlsx, txt Data Formats
- HMI With Touch Screen and Multilevel Password
- Single Site Provided (Max 20KV test)

sales@intotest.com
www.intotest.com

Disclaimer: The above graphic is for illustration and subject to change without affecting its performance.
**Final UPH to be discussed according to specification*

Intotest Sdn Bhd
Lot 62461, 1, Jln Tunku Abdul Rahman, Kampung Gangsa,
76100 Durian Tunggal, Malacca
Tel. +06-337 6866

REV2026082026